

Safety data sheet

Page: 1/12

BASF Safety data sheet
Date / Revised: 19.02.2020
Product: **49-W554 0,100L Basecoat**

Version: 1.0

(30668757/SDS_GEN_NZ/EN)

Date of print 11.03.2020

1. Substance/preparation and manufacturer/supplier identification

49-W554 0,100L Basecoat

Recommended use: Sprayable

Manufacturer/supplier:

BASF New Zealand Ltd.
Regus Auckland Airport
Level 1, Quad 7, 6 Leonard Isitt Drive
PO Box 407 Shortland Street, Auckland 2022
NEW ZEALAND
Telephone: +64 9 255-4300
Telefax number: +64 9 255-4307

Emergency information:

National Poisons Centre: 0800 764 766
BASF Emergency Advice Number: 0800 944 955 (24 hour advice in an emergency only)
BASF Emergency Advice Number: +61 3 8855 6666 (If calling from outside New Zealand)

2. Hazard identification

Classification of the substance and mixture:

Skin corrosion/irritation: Cat. 2

Serious eye damage/eye irritation: Cat. 1

Skin sensitization: Cat. 1B

Specific target organ toxicity — single exposure: Cat. 3 (Vapours may cause drowsiness and dizziness.)

Flammable liquids: Cat. 3

Label elements and precautionary statement:

Pictogram:



Signal Word:
 Danger

Hazard Statement:

H226 Flammable liquid and vapour.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H336 May cause drowsiness or dizziness.

Precautionary Statements (Prevention):

P280 Wear protective gloves, protective clothing and eye protection or face protection.
 P271 Use only outdoors or in a well-ventilated area.
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P264 Wash contaminated body parts thoroughly after handling.
 P242 Use only non-sparking tools.
 P241 Use explosion-proof electrical, ventilating and lighting equipment.
 P243 Take action to prevent static discharges.
 P233 Keep container tightly closed.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P240 Ground and bond container and receiving equipment.
 P272 Contaminated work clothing should not be allowed out of the workplace.

Precautionary Statements (Response):

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
 P370 + P378 In case of fire: Use water spray for extinction.
 P362 + P364 Take off contaminated clothing and wash it before reuse.
 P310 Immediately call a POISON CENTER or doctor/physician.
 P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
 P303 + P361 + P353 IF ON SKIN (or hair): Remove or Take off immediately all contaminated clothing. Rinse skin with water or shower.
 P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Precautionary Statements (Storage):

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
 P403 + P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.

Precautionary Statements (Disposal):

P501 Dispose of contents and container to hazardous or special waste collection point.

Other hazards which do not result in classification:

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

3. Composition/information on ingredients

Chemical nature

acrylic resin, organic solvent, pigment, polyurethane

Hazardous ingredients

1-methoxypropan-2-ol

Content (W/W): $\geq 25\%$ - $< 30\%$ Flam. Liq.: Cat. 3
 CAS Number: 107-98-2 Acute Tox.: Cat. 5 (oral)
 STOT SE: Cat. 3 (drowsiness and dizziness)

2-dimethylaminoethanol

Content (W/W): $\geq 1\%$ - $< 2\%$ Flam. Liq.: Cat. 3
 CAS Number: 108-01-0 Acute Tox.: Cat. 3 (Inhalation - vapour)
 Acute Tox.: Cat. 4 (oral)
 Acute Tox.: Cat. 4 (dermal)
 Skin Corr./Irrit.: Cat. 1B
 Eye Dam./Irrit.: Cat. 1
 STOT SE: Cat. 3 (irr. to respiratory syst.)
 Aquatic Acute: Cat. 3

1-methoxy-2-propylacetate

Content (W/W): $\geq 15\%$ - $< 20\%$ Flam. Liq.: Cat. 3
 CAS Number: 108-65-6 STOT SE: Cat. 3 (drowsiness and dizziness)

toluene

Content (W/W): $\geq 0.2\%$ - $< 0.3\%$ Asp. Tox.: Cat. 1
 CAS Number: 108-88-3 Flam. Liq.: Cat. 2
 Skin Corr./Irrit.: Cat. 2
 Repr.: Cat. 2 (unborn child)
 STOT SE: Cat. 3 (drowsiness and dizziness)
 STOT RE (Central nervous system): Cat. 2
 Aquatic Acute: Cat. 2
 Aquatic Chronic: Cat. 3

2-butoxyethanol

Content (W/W): $\geq 1\%$ - $< 2\%$ Flam. Liq.: Cat. 4
 CAS Number: 111-76-2 Eye Dam./Irrit.: Cat. 2A
 Acute Tox.: Cat. 4 (oral)
 Skin Corr./Irrit.: Cat. 2

2,4,7,9-Tetramethyldec-5-yne-4,7-diol

BASF Safety data sheet
Date / Revised: 19.02.2020
Product: **49-W554 0,100L Basecoat**

Version: 1.0

(30668757/SDS_GEN_NZ/EN)

Date of print 11.03.2020

Content (W/W): $\geq 2\%$ - $< 2.5\%$ Eye Dam./Irrit.: Cat. 1
CAS Number: 126-86-3 Skin Sens.: Cat. 1B
 Aquatic Acute: Cat. 3
 Aquatic Chronic: Cat. 3

4. First-Aid Measures

General advice:

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Remove affected person from danger area. Immediately remove contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. If symptoms persist, seek medical advice. If breathing is irregular or stopped, administer artificial respiration.

On skin contact:

If symptoms persist, seek medical advice. Remove contaminated clothing. Wash skin with soap and water, rinse abundantly. Do NOT use solvents or thinners.

On contact with eyes:

Remove contact lenses, if present. Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist. Immediate medical attention required.

On ingestion:

Do not induce vomiting. Rinse mouth thoroughly with water, seek medical attention. If adverse health effects develop seek medical attention.

Note to physician:

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Hazards: Danger of drowsiness and dizziness. skin irritation

Treatment: Symptomatic treatment (decontamination, vital functions).

Antidote: No known specific antidote.

5. Fire-Fighting Measures

Suitable extinguishing media:

carbon dioxide, alcohol-resistant foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons:

water jet

Specific hazards:

Fire will produce dense black smoke. Inhalation of dangerous decomposition products may cause serious damage to health.

Special protective equipment:

Appropriate breathing apparatus may be required.

Further information:

Cool closed containers in the vicinity of the source of fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.

6. Accidental Release Measures

Personal precautions:

Use personal protective clothing. Avoid breathing vapours. Ensure adequate ventilation. Advice on product handling can be found in sections 7 and 8 of this safety data sheet. Keep away from sources of ignition.

Environmental precautions:

Do not allow to enter drains or waterways. If the product enters drains or sewers, the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the Environment Agency. Do not discharge into the subsoil/soil.

Methods for cleaning up or taking up:

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal according with the waste regulations (see section 13). Clean preferably with a detergent; avoid the use of solvents. Ensure adequate ventilation.

7. Handling and Storage

Handling

Provide good ventilation of working area (local exhaust ventilation if necessary). Do not return residues to the storage containers. Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. Avoid inhalation of vapour and spray mist. The workplace should be equipped with an emergency shower and eye-rinsing facility. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:

Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. Solvent vapours are heavier than air and spread along floors. Vapour forms explosive mixtures with air. The relevant fire protection measures should be noted. Use explosion-proof equipment.

Storage

Keep away from oxidising agents, from strongly alkaline and strongly acid materials.

(30668757/SDS_GEN_NZ/EN)

Date of print 11.03.2020

Suitable materials for containers: High density polyethylene (HDPE), Low density polyethylene (LDPE), Polyethylenetherephtalate (PET), Polypropylene (PP), Carbon steel (Iron), tinned carbon steel (Tinplate)

Further information on storage conditions: Electrical equipment must be explosion-proof to the appropriate standard. Floors must be of conducting type and impermeable to the materials being stored. Keep container tightly closed. Never use pressure to empty; container is not a pressure vessel. Close containers carefully once opened and store upright in order to prevent any leakage. No smoking. Prevent unauthorized access. Detailed information can be gained from the relevant technical data sheets. Always keep in containers of same material as the original one. Observe label precautions. Store in a dry, well ventilated place. Protect from direct sunlight. Keep away from sources of ignition. Keep away from heat.

Storage stability:

Storage temperature: 5.00 - 35.00 °C

8. Exposure controls and personal protection

Components with occupational exposure limits

1-methoxypropan-2-ol, 107-98-2;

TWA value 50 ppm (ACGIHTLV)

STEL value 100 ppm (ACGIHTLV)

TWA value 369 mg/m³ ; 100 ppm (OEL (NZ))

STEL value 553 mg/m³ ; 150 ppm (OEL (NZ))

2-dimethylaminoethanol, 108-01-0;

TWA value 7.4 mg/m³ ; 2 ppm (OEL (NZ))

STEL value 22 mg/m³ ; 6 ppm (OEL (NZ))

toluene, 108-88-3;

TWA value 20 ppm (ACGIHTLV)

TWA value 188 mg/m³ ; 50 ppm (OEL (NZ))

Skin Designation (OEL (NZ))

Skin absorption can be significant.

2-butoxyethanol, 111-76-2;

TWA value 20 ppm (ACGIHTLV)

TWA value 121 mg/m³ ; 25 ppm (OEL (NZ))

Skin Designation (OEL (NZ))

Skin absorption can be significant.

Personal protective equipment

Respiratory protection:

Respiratory protection not required. When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators. Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet (sanding/ flatting) should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used. Use A1P2 breathing-protection half mask in case of contact with aerosols.

Hand protection:

Further information on penetration time is available from the manufacturer of the glove.
Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components.
The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).
Follow manufacturer's advice on use, storage, maintenance and replacement of gloves.
The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream).
Wear protective gloves. Any chemical protection glove certified according to EN 374 is suitable: e.g. The specifications of the Technical Rule for Hazardous Substances (TRGS) 401 must be observed (TRGS 401: Risks resulting from skin contact - identification, assessment, measures).
butyl rubber gloves - material thickness: 0,5 mm

Eye protection:

Tightly fitting safety goggles (splash goggles) (e.g. EN 166), Required when there is a risk of eye contact.

Body protection:

Body protection not required., Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

General safety and hygiene measures:

Do not breathe vapour/spray. Eye wash fountains and safety showers must be easily accessible. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove contaminated clothing immediately and dispose of safely. Hands and/or face should be washed before breaks and at the end of the shift. Keep separated from food stuffs and feed stocks.

9. Physical and Chemical Properties

Form:	liquid
Colour:	blue
Odour:	specific
pH value:	not applicable
Melting point:	not determined
onset of boiling:	119.00 °C
Flash point:	23 °C
Flammability (solid/gas):	Flammable liquid and vapour.
Lower explosion limit:	36 g/m ³
Ignition temperature:	> 200.00 °C
Self heating ability:	It is not a substance capable of spontaneous heating.
Explosion hazard:	not explosive
Fire promoting properties:	not fire-propagating

BASF Safety data sheet
Date / Revised: 19.02.2020
Product: **49-W554 0,100L Basecoat**

Version: 1.0

(30668757/SDS_GEN_NZ/EN)

Date of print 11.03.2020

Vapour pressure:	13.00 hPa (20 °C)	
	(50 °C) not determined	
Density:	1.059 g/cm ³ (20 °C)	
Miscibility with water:	immiscible	
Viscosity, kinematic:	411.6 mm ² /s (20 °C)	
	(40 °C) not determined	
Flow time:	> 60 s	(DIN EN ISO 2431; 6 mm)

10. Stability and Reactivity

Conditions to avoid:
Avoid direct sunlight.

Substances to avoid:
Keep away from highly acidic or alkaline substances as well as oxidants in order to prevent exothermal reactions.

Hazardous reactions:
Vapours may form ignitable mixture with air.

When exposed to high temperatures hazardous decomposition products such as smoke, carbon monoxide, carbon dioxide, oxides of nitrogen, hydrogen cyanide, monomeric isocyanates may be produced., No hazardous decomposition products if stored and handled as prescribed/indicated.

11. Toxicological Information

Acute toxicity

Assessment of acute toxicity:
Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated and prolonged exposure to solvents at levels significantly above OELs may lead to the development of long-lasting central nervous system disorders such as chronic toxic encephalopathy, signs of toxicity include changes in behaviour and memory. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Based on available Data, the classification criteria are not met.

Information on: 1-methoxypropan-2-ol

Experimental/calculated data:

LD50 rat (oral): 4,016 mg/kg (similar to OECD guideline 401)

Information on: 2-dimethylaminoethanol

Experimental/calculated data:

LD50 rat (oral): 1,183 mg/kg (OECD Guideline 401)

Information on: 2-dimethylaminoethanol

Experimental/calculated data:

LC50 rat (by inhalation): 6.1 mg/l 4 h (OECD Guideline 403)

The vapour was tested.

rat (by inhalation): 10 min (IRT)

No Mortality within the stated exposition time as shown in animal studies, however, deaths occurred after longer exposure.

Irritation

Assessment of irritating effects:

The liquid splashed in the eyes may cause irritation and reversible damage. Skin contact causes irritation. May cause severe damage to the eyes.

Respiratory/Skin sensitization

Assessment of sensitization:

Sensitization after skin contact possible.

Germ cell mutagenicity

Assessment of mutagenicity:

Based on available Data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity:

Based on available Data, the classification criteria are not met.

Reproductive toxicity

Assessment of reproduction toxicity:

Based on available Data, the classification criteria are not met.

Developmental toxicity

Assessment of teratogenicity:

Based on available Data, the classification criteria are not met.

Specific target organ toxicity (single exposure):

Assessment of STOT single:
Possible narcotic effects (drowsiness or dizziness).

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:
Based on available Data, the classification criteria are not met.

Aspiration hazard

No aspiration hazard expected.

12. Ecological Information

Ecotoxicity

Assessment of aquatic toxicity:
There are no test results available for this product. Do not allow to enter drains or waterways. Based on available Data, the classification criteria are not met.

Mobility

Assessment transport between environmental compartments:
No data available.

Persistence and degradability

Assessment biodegradation and elimination (H₂O):
Biological degradability of hazardous substances mentioned in section 3:

Information on: 2-dimethylaminoethanol

Elimination information:

60.5 % BOD of the ThOD (14 d) (OECD 301C; ISO 9408; 92/69/EEC, C.4-F) (aerobic, Inoculum conforming to MITI requirements (OECD 301C))

Information on: toluene

Elimination information:

80 % BOD of the ThOD (20 d) (APHA 'Standard Methods', No. 219, 1971) (aerobic, domestic sewage)

Literature data.

Information on: 2,4,7,9-Tetramethyldec-5-yne-4,7-diol

Elimination information:

< 10 % CO₂ formation relative to the theoretical value (28 d) (OECD 301B; ISO 9439; 92/69/EEC, C.4-C) (aerobic, activated sludge, domestic)

< 20 % CO₂ formation relative to the theoretical value (60 d) (ISO DIS 9439) (aerobic, activated sludge)

25.4 % DOC reduction (57 d) (OECD Guideline 302 A) (aerobic, activated sludge, domestic)

< 10 % (28 d) (OECD Guideline 302 B) (aerobic, activated sludge, domestic)

Bioaccumulation potential

Bioaccumulation potential:
No data available.

13. Disposal Considerations

Observe national and local legal requirements.

Contaminated packaging:

Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

14. Transport Information

Domestic transport:

Packing group: III
ID number: UN 1263
Transport hazard class(es): 3
Proper shipping name: PAINT

Further information

Hazchem Code:3Y
IERG Number:14

Sea transport

IMDG

Packing group: III
ID number: UN 1263
Transport hazard class(es): 3
Marine pollutant: NO
Proper shipping name: PAINT

Air transport

IATA/ICAO

Packing group: III
ID number: UN 1263
Transport hazard class(es): 3
Proper shipping name: PAINT

15. Regulatory Information

Other regulations

HSNO Approval Number HSR002662
Surface Coatings and Colourants (Flammable) Group Standard 2017

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

Tracking requirements do not apply to this substance.

A certified handler is not required for the handling of this substance.

16. Other Information

For multi-pack systems observe material safety data sheets of all components. Restricted to professional users.

Vertical lines in the left hand margin indicate an amendment from the previous version.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.